

DuPont™ Cyrel® FAST TD4260

THE WORLD'S FIRST WIDE-FORMAT SOLVENT-FREE FLEXOGRAPHIC PLATE PROCESSOR

DuPont Packaging Graphics

To help our customers gain competitive advantage in the global packaging graphics value chain.

DuPont Packaging Graphics continues to be a global technology leader in supplying flexographic printing systems. Our scientists continue to develop unique solutions based on new technologies to help our customers expand their business by taking advantage of new profitable packaging printing opportunities.

DuPont Packaging Graphics portfolio of products includes Cyrel® brand photopolymer plates (analog and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.

Cyrel® FAST plates in one hour or less!

The Cyrel® FAST system is a revolutionary technology that offers enhanced pressroom productivity.

Cyrel® FAST TD4260 is a platemaking system that uses dry, thermal technology to process high-quality flexo plates – eliminating solvents and aqueous solutions from the plateroom.

Cyrel® FAST TD4260 allows the production of Cyrel® FAST finished plates of up to 42 inch by 60 inch in less than one hour, making it the ideal just-in-time platemaking system for a market that demands quick turnaround and high quality.



DuPont™ Cyrel® FAST TD4260

Cyrel® FAST TD4260 delivers outstanding plate quality and uniformity. This processor has the ability to produce a finished plate without solvent washout. The wide format Cyrel® 2000 EC/LF for exposing and light-finishing plates is available to complement the Cyrel® FAST TD4260.

As with all elements of the Cyrel® FAST system, it is environmentally friendly with no solvents to handle, store or recycle. In addition, the new design saves space and requires no expensive plateroom construction.

The technology enhances the production of high-quality flexo plates quickly, by combining the efficiency and speed of digital plate imaging with the productivity and environmental benefits of dry, thermal plate processing.

DuPont™ Cyrel® DFM and Cyrel® DFH are the digital plates for the DuPont thermal platemaking process, designed to meet the needs of high quality flexo with fine halftone, linework and solids.

Applications

- Flexible packaging
- Carrier bags
- Folding cartons
- Pre-print liner
- Beverage cartons

Cyrel® FAST Performance Benefits

- Extremely rapid access time
- Excellent ink transfer permits superior printing uniformity
- Higher durability for long print runs
- High exposure resolution results in better quality reproduction
- Image relief is clean and sharp
- Exceptional thickness uniformity
- High resistance to ozone and white light results in excellent storage flexibility



The miracles of science™

DuPont Packaging Graphics

“Advancing Flexography”

General	Details	Other notes
Equipment Name	DuPont™ Cyrel® FAST TD4260	Thermal developer (water cooled)
Global material code	D12071679	Processor, Chiller and metal hand cart
Packing	Crate	
Max. throughput	Approximately 4 plates/hour	Full plate size
Max. nominal plate width	42 inch	
Min. nominal plate width	24 inch	
Max. nominal plate length	60 inch	
Min. nominal plate length	30 inch	
Max. plate thickness	0.112 inch	
Min. plate thickness	0.045 inch	
Telephone connection	RJ11 phone jack	Modem included
Electrical	220–240V, 50/60hz * 380–400V, 50/60hz **	Three phases and ground * Three phases, neutral and ground **
Current (nominal load)	30 amps per phase	Thermal magnetic circuit breaker has to be at least a 32 Amp rating
Grounding	≤ 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
Compressed air	80 psi (5.5 bar) @ 5 cfm moisture-free	Via DIN, ½" hose connection
Exhaust	6 inch (Connection)	125 cfm @ -3.25" H/2o
Environmental Data	Temperature range 65° F to 85° F	Relative humidity from 20% to 85% non-condensing
Dimension L x W x H	59 inch x 71 inch x 47 inch	
Net weight	3,000 lb	
Dimension L x W x H (W/crate)	71 inch x 81 inch x 61 inch	
Weight w/crate	4,000 lb	
Color	Grey and Red	DuPont grey and DuPont red

* Electrical configuration 1 ** Electrical configuration 2

All technical information set out herein is provided free of charge and is based on technical data, which DuPont believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents.

United States

DuPont Customer Technology Center
Chestnut Run Plaza, Bldg. 702
Wilmington, DE 19880-0702
800.345.9999

Canada

DuPont Packaging Graphics
P.O. Box 2200, Streetsville
Mississauga, Ontario Canada, L5M 2H3
905.821.5042

To learn more, visit www.cyrel.dupont.com
or contact your Cyrel® specialist



The miracles of science™